



Pattern: **Connection** Grade 4

Fabric Specifications	
Crypton, High Performance, INCASE	High Performance
Content	85% Polyester, 15% Cotton
Weight (oz/lin yd)	8.8
Width (inches)	54
Ends (per inch)	80
Picks (per inch)	50
Horizontal Repeat (inches)	Not Applicable
Vertical Repeat (inches)	Not Applicable
Directional (yes or no)	Yes
Railroaded (yes or no)	No
Cleaning Code	W
Finish	Crypton®
Backing	Crypton®
Certifications	
SCS Certified Indoor Advantage Gold	Yes
Performance Characteristics	
Abrasion Resistance	ASTM D4157
Abrasion Resistance (Double Rubs)	50,000
Tensile Strength	ASTM D5034
Tensile Strength Warp (lbs)	320.0
Tensile Strength Fill (lbs)	197.0
Tear Strength	ASTM D2262
Tear Strength Warp (lbs)	33.0
Tear Strength Fill (lbs)	29.0
Seam Slippage	ASTM D4034
Seam Slippage Warp (lbs)	60.0
Seam Slippage Fill (lbs)	43.0
Brush Pill	ASTM D3511
Brush Pill (Class)	4
Colorfastness to Crocking	AATCC 8
Colorfastness to Crocking Dry	4.0
Colorfastness to Crocking Wet	3.0
Colorfastness to Light	AATCC 16
Colorfastness (Hours)	40
Colorfastness (Class)	4
Flammability	
California Technical Bulletin 117 Section E (CS-191-53)	Passes
NFPA 260	Class 1
UFAC	Class 1

**For samples call:
800-841-8111**