

Pattern: Fandango Grade 2

Pattern: Talldally0 Grade 2	
Fabric Specifications	
Content	100% polyester
Weight (oz/lin yd)	.722
Width (inches)	54
Ends (per inch)	
Picks (per inch)	
·	
Horizontal Repeat (inches)	
Vertical Repeat (inches)	
Directional (yes or no)	
Railroaded (yes or no)	
Cleaning Code	W
Finish	Antimicrobial —
	Silver Based Ion Technology
Backing	Acrylic
Certifications	
SCS Certified Indoor Advantage Gold	
Performance Characteristics	
Abrasion Resistance	ASTM D 4157
Abrasion Resistance (Double Rubs)	60,000
Tensile Strength	ASTM D 5034
Tensile Strength Warp (lbs)	182
Tensile Strength Fill (lbs) Tear Strength	ASTM D 2262
Tear Strength Warp (lbs)	17
Tear Strength Fill (lbs)	35
Seam Slippage	ASTM D 4034
Seam Slippage Warp (lbs)	74
Seam Slippage Fill (lbs)	56
Brush Pill	ASTM D 3511
Brush Pill (Class)	4
Colorfastness to Crocking	AATCC 8
Colorfastness to Crocking Dry	Class
Colorfastness to Crocking Wet	Class
Colorfastness to Light	AATCC 16 option 1
Colorfastness (Hours)	40
Colorfastness (Class)	4
Flammability	
California Technical Bulletin 117	Passes
Section E (CS-191-53)	1 43363
NFPA 260	Class 1
UFAC	Class 1

For samples call:

800-841-8111