



Pattern: **Lyric** Grade 2

| Fabric Specifications | |
|---|---------------------------|
| Crypton, High Performance, INCASE | High Performance |
| Content | 58% Cotton, 42% Polyester |
| Weight (oz/lin yd) | 14.1 |
| Width (inches) | 54 |
| Ends (per inch) | 144 |
| Picks (per inch) | 38 |
| Horizontal Repeat (inches) | Not Applicable |
| Vertical Repeat (inches) | Not Applicable |
| Directional (yes or no) | Yes |
| Railroaded (yes or no) | No |
| Cleaning Code | S |
| Finish | Teflon® |
| Backing | Latex |
| Certifications | |
| SCS Certified Indoor Advantage Gold | No |
| Performance Characteristics | |
| Abrasion Resistance | ASTM D4157 |
| Abrasion Resistance (Double Rubs) | 50,000 |
| Tensile Strength | ASTM D5034 |
| Tensile Strength Warp (lbs) | 100.0 |
| Tensile Strength Fill (lbs) | 96.0 |
| Tear Strength | ASTM D2262 |
| Tear Strength Warp (lbs) | 22.4 |
| Tear Strength Fill (lbs) | 17.7 |
| Seam Slippage | ASTM D4034 |
| Seam Slippage Warp (lbs) | 100.0 |
| Seam Slippage Fill (lbs) | 55.0 |
| Brush Pill | ASTM D3511 |
| Brush Pill (Class) | 4 |
| Colorfastness to Crocking | AATCC 18E/AATCC 8 |
| Colorfastness to Crocking Dry | 4.0 |
| Colorfastness to Crocking Wet | 3.0 |
| Colorfastness to Light | AATCC 16 |
| Colorfastness (Hours) | 40 |
| Colorfastness (Class) | 4 |
| Flammability | |
| California Technical Bulletin 117 Section E (CS-191-53) | Passes |
| NFPA 260 | Class 1 |
| UFAC | Class 1 |

For samples call:
800-841-8111