



Pattern: **Structure** Grade 3

Fabric Specifications	
Crypton, High Performance, INCASE	Crypton®
Content	51% Acrylic, 49% Polyester
Weight (oz/lin yd)	15.1
Width (inches)	54
Ends (per inch)	
Picks (per inch)	
Horizontal Repeat (inches)	3.0
Vertical Repeat (inches)	3.125
Directional (yes or no)	Yes
Railroaded (yes or no)	No
Cleaning Code	W
Finish	Crypton®
Backing	Crypton®
Certifications	
SCS Certified Indoor Advantage Gold	
Performance Characteristics	
Abrasion Resistance	
Abrasion Resistance (Double Rubs)	50,000
Tensile Strength	
Tensile Strength Warp (lbs)	
Tensile Strength Fill (lbs)	
Tear Strength	
Tear Strength Warp (lbs)	
Tear Strength Fill (lbs)	
Seam Slippage	
Seam Slippage Warp (lbs)	
Seam Slippage Fill (lbs)	
Brush Pill	
Brush Pill (Class)	
Colorfastness to Crocking	
Colorfastness to Crocking Dry	
Colorfastness to Crocking Wet	
Colorfastness to Light	
Colorfastness (Hours)	
Colorfastness (Class)	
Flammability	
California Technical Bulletin 117 Section E (CS-191-53)	Passes
NFPA 260	Class 1
UFAC	Class 1

For samples call:
800-841-8111